	4			3		2			1	
ITEM	CONNECTOR PART NO.	_	DESCRIPTION					Table 1		
1	SNAC3-A021T-M0.64		OR CONTACT			JST Part Number	r	Description		L
2	20AWG (0.50mm²), AVSS	BLACK				ASNAC3SNAC320K	(51 2" Do	uble-End Pre-Cri	imp Lead	50.8±5.0
						ASNAC3SNAC320K2	102 4" Do	uble-End Pre-Cri	imp Lead	101.6 ± 5.
						ASNAC3SNAC320K2	152 6" Do	uble-End Pre-Cri	imp Lead	152.4 ± 5.
						ASNAC3SNAC320K2	203 8" Do	uble-End Pre-Cri	imp Lead	203.2 ± 5.
						ASNAC3SNAC320K2	254 10" Do	ouble-End Pre-Cr	rimp Lead	254 ± 5.0
						ASNAC3SNAC320K3	305 12" Do	ouble-End Pre-Cr	rimp Lead	304.8±5.
		 ⊲	< <	J	L (See Table 1) ± 5	0			1	
					2					
				0.75		SCALE 1: 1 DIMENSIONS All dimensions are in MM with a tolerance of +/- 5.0 unless otherwise specified. DRAWN BY STEVEN PILKINGTON CHECKED BY	DESCRIPTION Automotiv ASSEMBLY PART NO DRAWING NO.	re Standard Pre-Crimped Leads). See Table	s - HVM / BMSC / BN	ISA, 20AWG
REV.		DESCRIPTION		DATE 3	BY	1: 1 DIMENSIONS All dimensions are in MM with a tolerance of +/- 5.0 unless otherwise specified. DRAWN BY STEVEN PILKINGTON	Automotiv ASSEMBLY PART NC DRAWING NO.	o. See Table	s - HVM / BMSC / BN	ИSA, 20AWG

HAR-GAM005-1 | Date: 1/14/25 | Rev: 0 | Rev Date: