

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR SHOWN WITHOUT WRITTEN PERMISSION.


Item No.	Part No.	Description
1	SF3M-41GF-M2.0N	JFA Connector Contact
2	UL1007, 16 AWG	Black

Electrical Specifications
Current: MAX 7.5AAC/DC
Voltage: 3.81mm pitch - 250V AC/DC 5.08mm pitch - 600V AC/DC

**APPLICABLE HOUSINGS**

TYPE	NO. OF CIRCUITS	HOUSING PART NO.	KEYING	TYPE	NO. OF CIRCUITS	HOUSING PART NO.	KEYING
FREE HANGING TYPE (SINGLE ROW)	3	F31MSF-03V-KX	X	FREE HANGING TYPE (DOUBLE ROW)	6	F32MDF-06V-KXX	XX
		F31MSF-03V-KY	Y			F32MDF-06V-KYY	YY
	4	F31MSF-04V-KX	X		12	F32MDF-06V-KXY	XY
		F31MSF-04V-KY	Y			F32MDF-12V-KXX	XX
	5	F31MSF-05V-KX	X		6	F32MDF-12V-KYY	YY
		F31MSF-05V-KY	Y			F32MDF-12V-KXY	XY
	8	F31MSF-08V-KX	X		12	F32MDP-06V-KXX	XX
		F31MSF-08V-KY	Y			F32MDP-06V-KYY	YY
	10	F31MSF-10V-KX	X		6	F32MDP-06V-KXY	XY
		F31MSF-10V-KY	Y			F32MDP-12V-KXX	XX
PANEL MOUNTING TYPE (SINGLE ROW)	3	F31MSP-03V-KX	X	PANEL MOUNTING TYPE (DOUBLE ROW)	12	F32MDP-12V-KYY	YY
		F31MSP-03V-KY	Y			F32MDP-12V-KXY	XY
	4	F31MSP-04V-KX	X		20	F32MDP-20V-KXX	XX
		F31MSP-04V-KY	Y			-	-
	5	F31MSP-05V-KX	X		-	-	
		F31MSP-05V-KY	Y		-	-	
	8	F31MSP-08V-KX	X		-	-	
		F31MSP-08V-KY	Y		-	-	
	10	F31MSP-10V-KX	X		-	-	
		F31MSP-10V-KY	Y		-	-	

Note: Other housings and configurations are available. Please contact JST for details.



All dimensions are in millimeters with a default tolerance of +/- 5.0 unless otherwise specified.	CUSTOMER NAME			
	DESCRIPTION			
Drawn By: Larissa Mosley Checked By: Steven Pilkington	SIZE	CUSTOMER PART NO.	PART NO.	REV
	SCALE	DRAWING NO.		DATE
	1:1	GAM-818		3/28/2019

ZONE	REV	DESCRIPTION	DATE	APPROVED