		2	3		4	•	5	6	7	8	
Item No.	Part No.	Descript	Description					APPLICABLE HOUSINGS			
1	1 SMR-001T-0.6		HM Connector Contact				FOR MALE CONTACT		FOR FEMALE CONTACT		
2	2 SHR-001T-P0.6		HR Connector Contact				NO. OF CIRCUITS	HOUSING PART NO HMR-02V	NO. OF CIRCUITS	HOUSING PART NO HRP-02-S	
							3	HMR-03V	3	HRP-03-S	
3	UL1007, 22 AV	/G Black					4	HMR-04V	4	HRP-04-S	
Electrical Specifications							8 12	HMR-08V HMR-12V	8	HRP-08-S HRP-12-S	
Current: 3A AC	C/DC									1111 12 0	
Voltage: 250V	AC/DC										
					71	1.85 +/- 5.0					
				4		1.00 1/- 0.0	•				
					1	50.8 +/- 5.0					
				1		1	Ť				
				(1)		3	2				
				\bigcirc		5	\bigcirc				
							r			JST	
								millimeters with a default	CUSTOMER NAME	JST	
								millimeters with a default tolerance of +/- 5.0 unless		JST	
						8.00		millimeters with a default tolerance of +/- 5.0 unless otherwise specified.	CUSTOMER NAME		
ZONE	REV	DE	ESCRIPTION			DATE	APPROVED	millimeters with a default tolerance of +/. 5.0 unless otherwise specified.	DESCRIPTION	- 2" Inside Length -F	

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO J.S.T. AND SHALL NOT BE USED OR SHOWN WITHOUT WRITTEN PERMISSION.